



# TRANSELF TYPE B 75W80

Extreme pressure lubricant for manual gearboxes.

## USES

**Mechanical gearboxes in cars and vans**

- TRANSELF TYPE B 75W-80 is recommended for the lubrication of gearboxes and axles of passenger cars and vans under very severe conditions.
- It is particularly suitable when easier gearshifting is required at low temperature while maintaining optimum efficiency of the gearbox at high temperature.

## PERFORMANCES

**API GL-4+**

- API GL-4+
- TRANSELF TYPE B 75W-80 meets the requirements of PEUGEOT - CITROËN

## CLIENTS BENEFITS

**Driving comfort**

**Performances life time**

- Extreme-pressure and antiwear properties authorizing the gears to operate under the strictest conditions.
- High resistance to deterioration ensuring reliable performance when extensively used at high temperature.
- Remarkable antirust and anticorrosion protection.
- Very high viscosity index and very low pour point ensuring optimum lubrication at all temperatures (easy gear shifting in cold weather as well as at high temperature in high speed driving conditions).
- High shear stability.
- Complete harmless to elastomers even at high temperature.
- Very high resistance to foaming.

## CHARACTERISTICS

	Unités	Grade 75W-80
Density at 15 °C		0.891
Kinematic viscosity at 40 °C	mm <sup>2</sup> /s (cSt)	65
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s (cSt)	10.0
Viscosity index		137
Pour point	°C	-40

The values in this table are typical values given as an indication

TOTAL LUBRIFIANTS  
16, rue de la République  
92800 PUTEAUX  
1/1

TRANSELF TYPE B 75W80  
APRIL 2007  
N° MPR 04/07



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant