



DYNATRANS DA 80W-90



Lubricant for axles equipped with limited slip differential systems.

APPLICATIONS

Limited slip differential axles

- Lubrication of axles equipped with limited slip differential systems for worksite equipment and agricultural machinery and also for 4 wheel drive passenger cars.
- May also be used in traditional hypoid axles not equipped with limited slip axles.

PERFORMANCE

Classifications

API : GL-5-LS
MIL.L. : 2105D

Manufacturers approvals

ZF : TE-ML 05C / 12C / 16E / 21C

Meets manufacturers' specifications

- Agricultural tractors :
CLAAS-RENAULT, DEUTZ, FORD M2C 104A, STEYR...

- Worksite equipment:
CASE, JCB, LIEBHERR, TEREX, VOLVO ...

CUSTOMER BENEFITS

Cleanliness

Comfort

Security

- Guarantees the high cleanliness of the limited slip disks installed in the axle
- Prevents noise and vibration under intensive use
- Thanks to its Extreme Pressure additives it provides maximum protection of very highly loaded gears and gears subject to shocks
- Excellent compatibility with the disk friction materials
- Excellent performance with respect to seals

SPECIFICATIONS

DYNATRANS DA	Units	80W-90
Viscosity at 40°C	mm ² /s	164
Viscosity at 100°C	mm ² /s	16,2
Viscosity index		102
Pour point	°C	-30

The values of the specifications show in this table are typical values given as an indication only.