

TRANSMISSION SYN FE 75W-140



Synthetic oil for gears

APPLICATIONS

- Very high performance synthetic oil for axles and reduction gears.
- High loaded gears.
- Recommended when filters are added to the lubrication system.
- Recommended for organs requiring either an API GL-4 oil, either an API GL-5 one.

PERFORMANCES

API GL-5
API GL-4
SCANIA STO 1:0

CUSTOMER BENEFITS

- Very high viscosity index.
- Increased Extreme-Pressure and antiwear properties for an optimized lubrication of hypoid or non-hypoid axles.
- Excellent antifoam, anticorrosion, antirust properties.
- Excellent thermal stability.
- Very low loss in viscosity through shear.
- Excellent stability in operation.
- Extended drain interval.
- Fuel saving.

CHARACTERISTICS

TRANSMISSION SYN FE	Unit	Grade SAE 75W-140
Volumetric mass at 15°C	kg/m ³	885
Viscosity at - 40°C	mPa.s	130 000
Viscosity at 40°C	mm ² /s	183
Viscosity at 100°C	mm ² /s	26,3
Viscosity index	-	178
Pour point	°C	- 36

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX

TRANSMISSION SYN FE 75W-140
September 2005
N° NPR 09/05



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.