

# QUARTZ 5000 DIESEL 15W-40



## Multigrade oil for diesel engines

### USES

- **TOTAL QUARTZ 5000 DIESEL 15W-40** is suited to all diesel engines (passenger cars and light industrial vehicles).
- **TOTAL QUARTZ 5000 DIESEL 15W-40** is suited to turbo-charged and multi-valved diesel engines.
- **TOTAL QUARTZ 5000 DIESEL 15W-40** can be used in all operating conditions (city traffic, road, motorways), whatever the season.

### PERFORMANCES

<b>Specifications</b>	ACEA API	A3/B3 SL/CF
<b>OEMs</b>	NORM PSA PEUGEOT CITROEN B71 2295	



### CUSTOMER BENEFITS

- Meets the ACEA requirements, guarantee of an high and constant quality for the lubricant.
- Multigrade oil.
- High viscosity index.
- Excellent viscosity stability .
- Excellent detergency and dispersancy.
- Very high antiwear and anticorrosion properties.
- Very good antioxidant, antirust, antifoaming properties.

### CARACTERISTICS

TOTAL QUARTZ 5000 DIESEL 15W-40	Units	SAE Grade
		15W-40
Volumetric mass at 15°C	kg/m <sup>3</sup>	888
Viscosity at 40°C	mm <sup>2</sup> /s	110
Viscosity at 100°C	mm <sup>2</sup> /s	14,3
Viscosity index	-	135
Flash point Cleveland	°C	234
Pour point	°C	-30

*The typical characteristics mentioned represent mean values.*

**TOTAL LUBRIFIANTS**  
562, avenue du Parc de l'île  
92029 Nanterre Cedex  
1/1

**QUARTZ 5000 DIESEL  
15W-40**

Update : 01/2009

Sticker Reference : MPC /01/09



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard  
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant