

TRACTELF BLS

90



Lubricant for axles equipped with limited slip differential systems.

APPLICATIONS

Limited slip differential axles

- Lubrication of axles equipped with limited slip differential systems for worksite equipment and agricultural machinery and also for 4 wheel drive passenger cars.
- May also be used in traditional hypoid axles not equipped with limited slip axles.

PERFORMANCES

Classifications | API : GL-5-LS | MIL.L. : 2105D

Manufacturers approvals | ZF | : TE-ML 05C / 12C / 16E / 21C

Meets manufacturers' specifications

- Agricultural tractors :

CLAAS-RENAULT, DEUTZ, FORD M2C 104A, STEYR...

- Worksite equipment:

CASE, JCB, LIEBHERR, TEREX, VOLVO ...

CUSTOMER BENEFITS

Cleanliness

Guarantees the high cleanliness of the limited slip disks installed in the axle

Comfort

• Prevents noise and vibration under intensive use

Security

- Thanks to its Extreme Pressure additives it provides maximum protection of very highly loaded gears and gears subject to shocks
- Excellent compatibility with the disk friction materials
- Excellent performance with respect to seals

CHARACTERISTICS

TRACTELF BLS	Units	90
Viscosity at 40°C	mm²/s	164
Viscosity at 100°C	mm²/s	16,2
Viscosity index		102
Pour point	°C	-30

The values of the specifications show in this table are typical values given as an indication only.

TOTAL LUBRIFIANTS 16, rue de la République 92800 PUTEAUX 1/1

TRACTELF BLS 90 Sheet updated : 09/2009 Sticker reference : FT 11-08

