


TRANSELF BM 75W-90



Fully synthetic lubricant for heavily loaded axles.

UTILISATIONS

Axles in trucks and vans

- For lubricating axles in cars and trucks in the most heavy-duty conditions.
- For use in gearboxes when the manufacturer requires a synthetic oil of API GL-5 level and SAE grade 75W-90.

PERFORMANCES

API GL5

**APPROVED BY MAJOR
MANUFACTURERS**

- Satisfies the highest extreme pressure level of the international API specification.
- Manufacturer approvals:
 - MERCEDES BENZ page 235.8
 - MAN 342 type SL
 - ZF TE-ML 07A, 12B, 16F, 17B
- Meets the requirements of:
 - SCANIA STO 1:0

CUSTOMERS BENEFIT

**Very extended drain
interval**

Fuel Saving

- Extreme-pressure and anti-wear properties enabling gears to function under the most severe conditions.
- High resistance to degradation, ensuring stable performance after prolonged use at high temperature.
- Very high viscosity number and low pour point ensuring perfect lubrication at all temperatures.
- Good shear stability.
- Inert to seals even at high temperatures.
- Very high anti-foaming power thus guaranteeing a resistant lubricating film even at high speeds.

CHARACTERISTICS

	Units	Grade 75W-90
Density at 15 °C		0.867
Kinematic viscosity at 40°C	mm ² /s (cSt)	115
Kinematic viscosity at 100 °C	mm ² /s (cSt)	16.8
viscosity index		160
Pour point	°C	-50

The characteristics shown are mean values.