

DELTA SUPER 30



Monograde lubricant for Gasoline and Diesel engines.

UTILISATION

- Suitable for all Gasoline engines of passenger cars or light duty vehicles (**before model 1996**) and turbocharged or normally aspirated Diesel engines of civil works machines, trucks, locomotives.
- Suitable for all Diesel stationary engines (energy production).
- Also suitable for gear boxes, torque converters, hydraulic systems when the manufacturer requires an engine oil with an appropriate grade for these applications.

PERFORMANCES

Specifications

ACEA E2
API CF/SF

OEMs approvals

MERCEDES-BENZ MB-Approval 228.0
MAN 270
CATERPILLAR TO-2
ZF TE-ML 02C/4B
MIL-L 2104 E

CUSTOMER BENEFITS

Technical performances

- Monograde
- High viscosity index
- High stability in operation
- Exceptional detergency level
- Very high dispersancy level
- Excellent antiwear and anticorrosion properties
- Excellent antioxydant, antirust and antifoaming properties

CHARACTERISTICS

DELTA SUPER 30	Units	SAE Grade 30W
Volumetric mass at 15°C	kg/m ³	890
Viscosity at 100°C	mm ² /s	11.5
Viscosity index	-	99
Flash point	°C	>200
Pour point	°C	-18
T.B.N	mgKOH/g	11.2

The typical characteristics mentioned represent mean values