

FINAMATIC II D



Automatic Transmission Fluid.

APPLICATIONS

FINAMATIC II D is an ATF (Automatic Transmission Fluid) meeting the requirements of the former General Motors Dexron[®] - IID specification.

- **FINAMATIC II D** is suitable for the lubrication of automatic transmissions fitted in vehicles built in USA, Europe and Japan when the level GM Dexron[®] - IID is required.

PROPERTIES

FINAMATIC II D gives you the following advantages:

- High oxidation resistance.
- Very good friction and heat transfer properties.
- High degree of antiwear and extreme pressure properties.
- Excellent resistance to corrosion, foaming, shearing and rust formation.
- Good behaviour at low temperature.
- Compatibility with elastomers (seals).

SPECIFICATIONS

- BMW groupe 23 - 3.0
- BMW groupe 24 - 3.0
- FORD MERCON[®]
- DEXRON[®] - II D
- MAN 339 Type V-1 (ex MAN 339 Type D)
- MAN 339 Type Z-1 (ex MAN 339 Type D)
- MERCEDES-BENZ p 236.6
- VOITH H55.633534 (ex G 607)
- ZF TE-ML-03D, 04D, 09, 11A, 14A, 17C

CHARACTERISTICS

Methods	Characteristics	FINAMATIC II D
Visual	Colour	red
ASTM D 1298	Volumetric mass at 15°C	0.873
ASTM D 445	Viscosity at 40°C, mm ² /s	40
ASTM D 445	Viscosity at 100°C, mm ² /s	8.1
ASTM D 97	Pour point, °C	-43
ASTM D 2270	Viscosity index	182
ASTM D 92	Flash point (COC), °C	190

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1

FINAMATIC II D
NOVEMBER 2006
N° MPR 11/06



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant