

FINAMATIC HP



Automatic Transmission Fluid.

APPLICATIONS

FINAMATIC HP is an ATF (Automatic Transmission fluid) approved by General Motors under licence number G-34564.

- **FINAMATIC HP** is suitable for the lubrication of many automatic transmissions fitted in vehicles produced in USA, Europe and Japan.

PROPERTIES

FINAMATIC HP gives you the following advantages :

- Superior oxidation resistance.
- Outstanding friction and heat transfer properties.
- High degree of antiwear and extreme pressure properties.
- Outstanding resistance to corrosion and foaming.
- Very favourable behaviour at low temperature.
- Compatibility with elastomers (seals).

SPECIFICATIONS

- Niveau GM DEXRON® III et FORD MERCON®
- ALLISON C4MAN 339 Type Z-1 (ex MAN 339 Type F)
- MAN 339 Type V-1 (ex MAN 339 Type F)
- VOITH H55.633534 (ex ANCIEN G 607)
- ZF TE-ML 03D, 04D, 09, 14A, 17C
- MB-Approval 236.5
- MB-Approval 236.9

CHARACTERISTICS

Methods	Characteristics	FINAMATIC HP
Visual	Colour	red
ASTM D 4052	Specific gravity at 15°C	0.860
ASTM D 445	Viscosity at 40°C, mm ² /s	34
ASTM D 445	Viscosity at 100°C, mm ² /s	7.7
ASTM D 97	Pour point, °C	-51
ASTM D 2270	Viscosity index	207
ASTM D 92	Flash Point, °C	196

The typical characteristics mentioned represent mean values