

PONTONIC TI 75W-80



Extreme pressure semi-synthetic lubricant for mechanical gearboxes.

APPLICATIONS

FINA PONTONIC TI is a partly synthetic oil containing extreme pressure additives for transmissions fitted to road vehicles.

- **FINA PONTONIC TI** is particularly suitable for use in commercial vehicles gearboxes, subjected to severe operating conditions.
- It fulfils the special requirements of ZF gearboxes with "Intarder" and allows extended drain intervals.

PROPERTIES

FINA PONTONIC FDL gives you the following advantages :

- Prevention of wear of pinions and bearings.
- Antirust and anticorrosion protection.
- Compatibility with copper and its alloys.
- Oxidation resistance.
- Very extended drain interval.
- Fuel saving.

SPECIFICATIONS

- API GL-4
- MAN 341 Type Z-3 (ex MAN 341 Type TL)
- ZF TE-ML 02D
- Meets the requirements for RENAULT TRUCKS gearboxes

CHARACTERISTICS

PONTONIC TI 75W-80	Grade SAE	75W-80
ASTM D 4052	Specific gravity at 15°C	0.883
ASTM D 445	Viscosity at 40°C, mm ² /s	64
ASTM D 445	Viscosity at 100°C, mm ² /s	9.5
ASTM D 97	Pour point, °C	-41
ASTM D 2270	Viscosity index	124
ASTM D 92	Flash Point (COC), °C	234

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1

PONTONIC TI 75W-90
NOVEMBER 2006
N° MPR 11/06



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant