

PONTONIC MP 80W-90



GEAR OIL.

APPLICATIONS

FINA PONTONIC MP is an extreme pressure mineral oil for transmissions fitted in commercial vehicles.

- **FINA PONTONIC MP** is specially designed for the lubrication of hypoid gear in axles.
- It also ensures lubrication of other gear assemblies such as manual gearboxes, transfer boxes, steering pumps and helical gears in axles when an API GL-5 level is required.

PROPERTIES

FINA PONTONIC MP gives you the following advantages :

- Very high extreme pressure performance.
- Excellent resistance to wear of pinions and bearings.
- Anti-rust and anti-corrosion protection.

SPECIFICATIONS

- API GL-5
- MAN 342 Type M-1 (ex MAN 342 type N)
- ZF TE-ML 05A, 07A, 16B, 17B

CHARACTERISTICS

	SAE Grades	80W-90
ASTM D 4052	Specific gravity at 20°C	0.901
ASTM D 445	Viscosity at 40°C, mm ² /s	144
ASTM D 445	Viscosity at 100°C, mm ² /s	15
ASTM D 97	Pour point, °C	-26
ASTM D 2270	Viscosity index	102
ASTM D 92	Flash Point COC, °C	220

The typical characteristics mentioned represent mean values