

# PONTONIC BV 75W-80



## GEAR OIL.

### APPLICATIONS

FINA PONTONIC BV is a mineral oil specially developed for the lubrication of gearboxes fitted in recent vehicles when thermal constraints are high.

- FINA PONTONIC BV is particularly suitable for the lubrication manual gearboxes which require an oil which remains fluid at low temperature, of grade SAE 75W-80, and with high extreme pressure properties.

### PROPERTIES

FINA PONTONIC BV gives you the following advantages :

- Easy gear changing at cold temperatures.
- Excellent antiwear and anti-corrosion protection especially for surfaces of synchromesh cones.
- Very good resistance to oxidation.

### SPECIFICATIONS

FINA PONTONIC BV meets the requirements of Several automotive manufacturers demanding oils to SAE grade 75W-80.

### CHARACTERISTICS

PONTONIC BV 75W-80	SAE Grade	75W-80
ASTM D 4052	Specific gravity at 15°C	0.887
ASTM D 445	Viscosity at 40°C, mm <sup>2</sup> /s	49
ASTM D 445	Viscosity at 100°C, mm <sup>2</sup> /s	8
ASTM D 97	Pour point, °C	-45
ASTM D 2270	Viscosity index	137
ASTM D 92	Flash Point COC, °C	208

*The typical characteristics mentioned represent mean values*