


TOTAL CLASSIC 5W-30



TOTAL

“TOTAL CLASSIC, the guaranteed quality”

Synthetic technology multigrade oil for gasoline and diesel engines, formulation using a set of additives with carefully selected performance and proportions to answer to the quality standards of the Association of the European Manufacturers.

APPLICATIONS

All Gasoline/Diesel engines
Direct injection Diesel

The most severe journeys
All times of year

“Vigorous” driving

- Developed to cover the most stringent requirements of **both recent gasoline and diesel engines** (since MY 2000).
- Particularly suited to **turbocharged, multi-valve and direct injection engines**.
- Perfectly **adapted to all vehicles equipped with catalysts** and using unleaded fuel or liquefied petroleum gas
- Can be used in the **most difficult operating conditions** (motorways, dense city traffic...), **whatever the season**.
- For all driving styles, particularly “vigorous” and high speeds.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International
Specifications

ACEA 2007 A5/B5 - A1/B1
API SL/CF

CUSTOMER BENEFITS

High performance
Lengthens engine life
Extended oil change
intervals

- Excellent engine protection and oxidation resistance
- Easy cold starts and fuel economies due to its extreme fluidity
- Immediate lubrication of engine parts during cold starts at low engine temperature, leading to longer engine life
- Meets the main technical requirements of the manufacturers as regards extended oil change intervals.

CHARACTERISTICS

TOTAL CLASSIC 5W-30	Units	SAE Grade 5W-30
Volumetric mass at 15°C	kg/m ³	853
Viscosity at 40°C	mm ² /s	57
Viscosity at 100°C	mm ² /s	9.9
Viscosity index	-	160
Flash point Cleveland	°C	224
Pour point	°C	-36

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
16, rue de la République
F- 92800 PUTEAUX
1/1

TOTAL CLASSIC 5W-30
Sheet updated : 10/08
Sticker reference: MPC 10/2008



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.