

HI PERF 2T RACING



Data sheet

Synthetic fortified oil for 2-stroke motorcycle engines

APPLICATIONS

Two-stroke motorcycle

- All types of two-stroke motorcycle engines of all cubic capacities: motorcycles, scooters subject to harsh operating condition.
- For premixing with gasoline at the ratio recommended by the engine manufacturer, or for adding to separate oil tank.
- Low smokes and perfumed.

PERFORMANCES

Specifications

- ISO-L-EGB
- JASO FB
- API TC

CUSTOMER BENEFITS

- Synthetic fortified with viscosity particularly adapted to:
 - ✓ Lubrication of 2-stroke engines equipped with an independent lubrication system
 - ✓ Premixing with gasoline
- Makes a permanent oil film, preventing any risk of seizure or binding.
- Avoids ring sticking
- Specially formulated to avoid sparks plug fouling.
- Burns without leaving any sticky deposits
- Very good anticorrosion, antirust and anti-wear properties
- Pre-diluted to ensure a stable and homogeneous mixture
- Perfectly adapted to unleaded fuel
- Environmentally friendly lubricant with reduction of smoke exhaust emissions

CHARACTERISTICS

HI PERF 2T RACING	Units	
Colour	-	Green & Perfumed
Volumetric mass at 15°C	Kg/m ³	873
Viscosity at 40°C	mm ² /s	66.5
Viscosity at 100°C	mm ² /s	9.5
Viscosity index	-	123
Flash point Cleveland	°C	115
Pour point	°C	-21

The typical characteristics mentioned represent mean values.

HI PERF 2T RACING
14 May 2004

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.