

HI PERF 4T RACING 10W40



Data sheet

Synthetic technology based oil for 4-stroke motorcycle engines

APPLICATIONS

High performance 4-stroke engines

- All types of high performance 4-stroke motorcycle engines of all cubic capacities, subject to the most severe conditions of use: racing, city traffic highway.
- Adapted for gear boxes lubrication and oil immersed clutches (no clutch slippage)

PERFORMANCES

Specifications

- API SL
- ACEA A2

CUSTOMER BENEFITS

- Synthetic technology based engine oil
- Super multi-grade
- Very high viscosity index
- Excellent viscosity stability in operation
- Excellent resistance of the oil film at high temperature
- Very high level of detergency and dispersancy.
- Excellent resistance to oxidation
- Very good anti-wear, anticorrosion, antirust and anti-foaming properties
- No risk of destructive pre-ignition

CHARACTERISTICS

HI PERF 4T RACING	Method	Units	SAE Grade 10W40
Volumetric mass at 15°C	ASTM D1298	Kg/m ³	875
Viscosity at 40°C	ASTM D445	mm ² /s	99
Viscosity at 100°C	ASTM D445	mm ² /s	14.5
Viscosity index	ASTM D2270	-	154
Pour point	ASTM D97	°C	-33
Flash point Cleveland	ASTM D92	°C	210

The typical characteristics mentioned represent mean values.

HI PERF 4T RACING
14 May 2004

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.