

QUARTZ 7000 SM 10W40



Data sheet

Premium Synthetic Based multigrade oil for passenger car engine

APPLICATIONS

Gasoline / diesel engine cars

- A premium synthetic based engine oil formulated from a combination of synthetic and conventional quality base stocks combined with modern performance additives to meet the requirements of latest API Service Category SM/CF.

Arduous service conditions

- Recommended for all petrol engines (multi-valve and turbo types, with or without catalytic converter) and all diesel engines, turbo-charged or naturally aspirated in cars and light vans.
- Recommended for use in the arduous service conditions inducted by the extremes of motorway and "stop/start" operation of high performance engines.

PERFORMANCES

International specifications

- API SM/CF (API Service Symbol)

Recommended for use

- Ford, GM, PSA, BMW, VW, Audi and Mercedes-Benz

CUSTOMER BENEFITS

Optimised performance

- Improved engine cleanliness through excellent detergency chemistry with an ultra refined and synthetic base oil mix
- Unique innovation in lubrication technology, identify a way of offering total engine protection during the three stages of the drive cycle – start-up, warm-up and normal driving conditions.

Lengthens engine life

- Excellent thermal and oxidation stability.
- An unique combination of advanced synthetic and meticulously selected additives provide freedom of ring sticking, reduction in deposits leading to a reduced engine wear and to a longer engine and component life.

Compatibility with a wide range of seal materials

- Ensures the important engine seals stay soft and pliable to minimize oil leakage.

CHARACTERISTICS

Total Quartz 7000 SM	Method	Units	SAE 10W40
Volumetric mass at 15°C	ASTM D1298	kg/m ³	868
Viscosity at 40°C	ASTM D445	mm ² /s	103
Viscosity at 100°C	ASTM D445	mm ² /s	14.8
Viscosity Index	ASTM D2270	-	149
Pour Point	ASTM D97	°C	-30
Flash Point	ASTM D92	°C	220

The typical characteristics mentioned represent mean values.

Total Quartz 7000 SM 10W40
Version April, 2009

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.