

QUARTZ 9000 SM 5W30



Data sheet

Advanced Fully Synthetic multigrade oil for passenger car engine

APPLICATIONS

Gasoline / diesel engine cars

- Is an advanced fully synthetic SAE 5W30 high performance engine oil. It combines outstanding low temperature fluidity and high load protection.
- Recommended for virtually all modern, technically advanced, petrol engines (multi-valve and turbo types, with or without catalytic converter) and all diesel engines, turbo-charged or naturally aspirated in cars and light vans. Specially suited where lower viscosity oil is recommended.

Arduous service conditions

- Designed to provide protection under severe driving style or conditions.
- Stability and endurance under extreme conditions (heat, load, speed) that can cause conventional oils to break down.

PERFORMANCES

International specifications

- API SM/CF (API Service Symbol)
- ILSAC GF-4 (Starburst Certification Symbol)

Recommended for use

- Ford, GM, PSA, BMW, VW, Audi and Mercedes-Benz

CUSTOMER BENEFITS

Optimised performance

- Provides excellent start-up performance and engine efficiency, particularly for vehicles used in city and suburban driving conditions.
- Excellent thermal and oxidation stability.

**Emissions/Fuel economy
Lengthens engine life**

- Developed to meet the most advanced emissions and fuel efficient requirements.
- An unique combination of advanced synthetic and meticulously selected additives provide freedom of ring sticking, reduction in deposits leading to a reduced engine wear and to a longer engine and component life.

**Low temperature flow properties
Compatibility with a wide range of seal materials**

- Circulates rapidly within the engine to minimize cold start up wear. Improves low temperature engine efficiency over conventional mineral oil.
- Ensures the important engine seals stay soft and pliable to minimize oil leakage.

CHARACTERISTICS

Total Quartz 9000 SM	Method	Units	SAE 5W30
Volumetric mass at 15°C	ASTM D1298	kg/m ³	853
Viscosity at 40°C	ASTM D445	mm ² /s	72.50
Viscosity at 100°C	ASTM D445	mm ² /s	12.01
Viscosity Index	ASTM D2270	-	163
Pour Point	ASTM D97	°C	-36
Flash Point	ASTM D92	°C	227

The typical characteristics mentioned represent mean values.

Total Quartz 9000 SM 5W30
Version April, 2006

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.