

TRANSMISSION DA 85W140



Data sheet

Oil for limited slip differentials self blocking axles

APPLICATIONS

Limited slip differentials

- Oil specially adapted to the lubrication of self-blocking axles equipped with limited self-differentials.

PERFORMANCES

International Specifications

- API GL-5
- ZF TE-ML 05C,12C

CUSTOMER BENEFITS

Technical Profile

- High viscosity index
- Very high extreme-pressure properties
- Specific friction properties
- High thermal stability
- Excellent oxidation resistance, antiwear, antifoam and antirust properties

CHARACTERISTICS

Total Transmission DA	Method	Units	SAE Grade 85W140
Volumetric mass at 15°C	ASTM D1298	Kg/m ³	913
Viscosity at 40°C	ASTM D445	mm ² /s	298
Viscosity at 100°C	ASTM D445	mm ² /s	25.00
Viscosity index	ASTM D2270	-	105
Flash point Cleveland	ASTM D97	°C	210
Pour point	ASTM D92	°C	-12

The typical characteristics mentioned represent mean values.

Total Transmission DA 85W140
Version Sept, 2005

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.