

NEVASTANE® CLEAR 15 & 68



FOOD INDUSTRY

TOTAL

USP White Mineral Oil for the Food and Pharmaceutical Industries.

APPLICATIONS

USP White Mineral Oil.

3H & H1 Registered Food Grade Oil.



ADVANTAGES

- **NEVASTANE CLEAR 15 & 68** are made with USP white mineral oil, **NSF listed 3H and H1**. They are recommended for use as a release agent in food processing plants where there is direct contact with foodstuff, such as dough dividers. These products comply with **FDA 21 CFR 172.878** and **FDA 21 CFR 178.3620(a)**. The minimal amount possible should be used to achieve the desired technical effect on the equipment.
- **NEVASTANE CLEAR 15 & 68** oils are suitable for use on machinery used for producing, manufacturing, packing, preparing, and packaging food where there is a possibility of incidental food contact. These products should be used as recommended by a responsible company representative. Prolonged contact with the skin may cause mild irritation. See the Material Safety Data Sheet for additional information.
- **NSF 3H, H1 Registered meets USDA 1998 H1 Guidelines for incidental contact with food.**

- Water white.
- Low and high temperature service.
- High temperature stability.
- 3H and H1 registered.
- Compatible with elastomers and seals.
- Good film strength.

TYPICAL CHARACTERISTICS	METHODS	NEVASTANE CLEAR	
		15	68
ISO VG Grade		15	68
NSF Registration Number		139922	140032
Appearance	Visual	Bright, Clear, Water White	
Viscosity @ 40°C, cSt	ASTM D 445	14.2-17.0	65.0-70.0
Saybolt Color, min.		30	30
Flash Point, COC, °F(°C)	ASTM D 92	350(178)	450(234)
Pour Point, °F(°C)	ASTM D 97	10(-12)	10(-12)
Density @ 60°F, lbs./gal.	ASTM D 1298	7.17	7.26
Specific Gravity @ 60°F/60°F	ASTM D 1298	0.859	0.863

Shelf Life: Use by 60 months or 5 years.

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127